



## Features

The Jazz DI Wall Mount is one variation of a complete family of direct/indirect fluorescent luminaires. Constructed of perforated steel and aluminum extrusions, it features a reveal between modules in continuous rows. The Jazz DI Wall Mount series can be furnished with a wide variety of perforated accent patterns in addition to the standard pattern. The standard pattern is a continuous perforation 3" wide. The perforations are 1/16" holes on 3/32" straight centers. Laser cut corporate logos can also be supplied as a feature for reception areas and conference rooms. The computer designed optical system creates a widespread indirect distribution, while the variety of direct components provides useful contrast.

## Specifications

**HOUSING:** One piece die formed 20-gauge cold rolled steel welded construction forming a 6 1/2" x 3 1/2" rounded profile. Continuous perforated sections are 1/16" x 3/32" straight centers with white .020 translucent overlay. Decorative finished end caps are extruded aluminum with no exposed hardware or knockouts.

**REFLECTOR:** Die formed 20 gauge cold rolled steel minimum 90% reflectivity finished in high gloss baked white enamel. Die formed specular reflector is also available.

**ELECTRICAL:** Ballast is electronic, universal voltage 120/277, high power factor, thermally protected, sound rated A with less than 10% total harmonic distortion. Luminaires in rows are pre-wired with quick connect through wiring. The minimum number of ballasts will be used unless otherwise specified.

**BALLAST DISCONNECT:** Luminaires are pre-wired with integrated locking disconnects.

**MOUNTING:** Standard installation is key slots 42" OC for ease of installation.

**FINISH:** Fixture housing and steel components are finished in baked white enamel applied over a five-stage pretreatment process.

**LAMPS:** Fixtures are provided for use with one or two T8, T5, T5HO, or compact fluorescent lamps. (Supplied by Others)

**CERTIFICATION:** Luminaires are U.L. Listed, C.S.A. certified and are Union Made in the United States of America I.B.E.W.

TYPE

## Ordering Guide

MODEL NO.	DIRECTION	NUMBER OF LAMPS	LAMPS	MOUNTING	ROW LENGTH	FINISH	VOLTAGE	OPTIONS
<b>JAZ</b>	<b>DI</b>							
<b>JAZ</b>	<b>DI = Direct/ Indirect</b>	<b>1</b> <b>2</b>	<b>T8</b> <b>T5</b> <b>T5HO</b>	<b>WM = Wall Mount</b>	<b>2 = 2 ft</b> <b>3 = 3 ft</b> <b>4 = 4 ft</b> <b>6 = 6 ft</b> <b>8 = 8 ft</b> For other, please enter row length (eg. 48 = 48 ft)	<b>W = White</b> <b>CC = Custom Color</b>	<b>UNV = 120/277</b>	<b>DIM = Dimming Ballast</b> <b>EPC = Emergency Battery Pack</b> <b>EMC = Emergency Circuit</b> <b>TCW = Two Circuit Wiring</b> <b>OTH = Other options available, see page 355</b>

**Example »** **JAZ** | **DI** | **2T8** | **WM** | **4** | **W** | **UNV**

Jazz direct/indirect with continuous perforated shielding for two 32 watt T8 lamps wall mounted four foot fixture finished in baked white enamel universal voltage electronic ballast less than 10% harmonic distortion.

