



TYPE _____

FEATURES

The Jazz AS is one variation of a complete family of indirect fluorescent luminaires. Constructed of steel and aluminum extrusions, it features a reveal between modules in continuous rows. The Jazz AS series is of solid construction with aluminum trim. The computer designed optical system creates a widespread indirect distribution.

SPECIFICATIONS

Housing: One piece die formed 20-gauge cold rolled steel construction forming a 16" x 3 3/4" rounded profile. The housing trim is die formed extruded aluminum with aluminum recessed ends. Decorative connectors join fixtures in rows.

Reflector: Die formed 20 gauge cold rolled steel minimum 90% reflectivity finished in high gloss baked white enamel. Die formed specular reflector is also available.

Electrical: Ballast is electronic, high power factor, thermally protected class P, sound rated A, with less than 20% total harmonic distortion. The minimum number of ballasts will be used unless otherwise specified.

Mounting: Standard Installation is an adjustable self-locking aircraft cable assembly 48" x 3/32" in diameter with 5" canopy. One 16/4 SJT straight 54" cord is supplied with each power feed. Standard pendants are available in 24" lengths. See Accessories for additional mounting.

Finish: Fixture housing and steel components are finished in baked white enamel applied over a five-stage pretreatment process.

Lamps: Fixtures are provided for use with two 32-watt T8 lamps or 54-watt T5 HO lamps. Also available with 40 watt or 50 watt compact fluorescent lamps. (Supplied by Others)

Certification: Luminaires are U. L. Listed, C. S. A. certified and are Union Made in the United States of America I.B.E.W.

ORDERING GUIDE

MODEL NO.	DIRECTION	LAMPS	MOUNTING	LENGTH	FINISH	VOLTAGE	OPTIONS
JAZ AS	I	232T8 228T5 254T5HO 440CF 450CF	AC= Cable PD= Pendant	4= ft 8= ft	W= White CC= Custom Color	120v 277v	See Options Below
	I= Indirect		See Accessories	for other, please enter row length (eg. 48=48ft)			

Example: **JAZ-AS-I-232T8-AC-4-W-120V**

Jazz All Solid for two 32 watt T8 lamps including two 48inch aircraft cables and power feed four foot fixture finished in baked white enamel 120v electronic ballast less than 20% total harmonic distortion.

OPTIONS

- E10=** Electronic ballast, high power factor, thermally protected class P, sound rated A, < 10% total harmonic distortion
- DIM=** Dimming Ballast
- EPC=** Emergency Battery Pack
- EMC=** Emergency Circuit
- TCW=** Two Circuit Wiring
- TDW=** Tandem Wiring
- OTH=** See Accessories for other options available

