



**TYPE** \_\_\_\_\_

**FEATURES**

The AP 1 square steel architectural linear series is an aesthetically designed luminaire. The AP 1 series is a bi-directional wall mounted task lighting fixture distributing the light down and out for optimum performance. The simplicity of the AP 1 series is the solution for task areas while providing maximum design versatility to meet the perceived source of illumination for a specific environment.

**SPECIFICATIONS**

**Housing:** One piece die formed 20-gauge cold rolled steel welded construction forming a 6" x 5" square profile. Finished end caps are laser cut 18-gauge cold rolled steel, with no exposed hardware or knockouts. Intermediate end caps are provided for precision alignment of continuous rows.

**Reflector:** The rear-curved reflector is .025 specular anodized aluminum.

**Electrical:** Ballast is electronic, high power factor, thermally protected class P, sound rated A, with less than 20% total harmonic distortion. The minimum number of ballasts will be used unless otherwise specified.

**Mounting:** Standard mounting is surface mounted. See Accessories for additional mounting.

**Finish:** Fixture housing and steel components are finished in baked white enamel applied over a five-stage pretreatment process.

**Lamps:** Fixtures are provided for use with one or two 32 watt T8 lamps or 54 watt T5 HO lamps. (Supplied by Others)

**Certification:** Luminaires are U. L. Listed, C. S. A. certified and are Union Made in the United States of America. I.B.E.W.

**ORDERING GUIDE**

MODEL NO.	DIRECTION	LAMPS	MOUNTING	LENGTH	FINISH	VOLTAGE	OPTIONS
<b>AP 1</b>	<b>D</b>	<b>132 T8</b> <b>232 T8</b> <b>154T5 HO</b> <b>254T5 HO</b>	<b>S</b> = Surface Mounted <b>AC</b> = Cable <b>PD</b> = Pendant	<b>4</b> = ft <b>8</b> = ft	<b>W</b> = White <b>CC</b> = Custom Color	<b>120v</b> <b>277v</b>	<b>See Options Below</b>
		<b>O</b> =Other Specify	See Accessories	for other, please enter row length (eg. 48=48ft)			

Example: **AP 1 D 232T8-S-4-W-120V**  
AP 1 direct luminaire for two 32 watt T8 lamps surface mounted four foot fixture finished in baked white enamel 120v electronic ballast less than 20% total harmonic distortion.

**OPTIONS**

- E10=** Electronic ballast, high power factor, thermally protected class P, sound rated A, < 10% total harmonic distortion
- DIM=** Dimming Ballast
- EPC=** Emergency Battery Pack
- EMC=** Emergency Circuit
- TCW=** Two Circuit Wiring
- TDW=** Tandem Wiring
- OTH=** See Accessories for other options available

