DAY-O-LITE

Profile Series | PRFL-22-D-WM

Date	Notes
Project	
Type Qty	

Features

ADA compliant linear wall luminaire.

Durable extruded aluminum housing.

LED optimized optics for smooth, efficient illumination.

Individual fixtures, continuous rows or custom patterns.

Programmable driver for custom lumen packages.

0-10V dimming to 1% standard. Dim-to-off available.

DMX, Lutron and DALI protocols also available.

Sensor Ready for wireless Smart Lighting Solutions.

80/90CRI, Tunable White and RGB available.

Bios SkyBlue™ circadian solutions available.

Declare Red List Approved.



FL Lens
All options page 5.



Ordering Guide

RS Declare. BAA

MODEL	OPTICS	LED[1]	LUMENS[2]	LENGTH	MOUNTING[3]	FINISH	OPTIONS
PRFL-22-D					WM		
PRFL-22-D Direct	**FL** = Frosted Acrylic Flush Lens DS1 = 1" Square Drop Lens DR1 = 1" Round Drop Lens DS2 = 2" Square Drop Lens DR2 = 2" Round Drop Lens All optics options detail on page 5.	**STATIC WHITE** 27 = 2700K 80CRI **30** = 3000K 80CRI **35** = 3500K 80CRI **40** = 4000K 80CRI 50 = 5000K 80CRI **BIOS SkyBlue** Circadian solutions **TUNABLE 2**-Channel 2700K-6500K Fixed CCT Range 2DIM10 = for 0-10V 2DMX = for DMX 2ESN = for Philips 2CAS = for Casambi 2LUT = for Lutron **TUNABLE 3**-Channel 1800K-6500K 92 CRI Selectable CCT Range 3DIM10 = for 0-10V **DIM-TO-WARM** DTW = Dim-to-Warm (2700K-6500K) 0-10V 3DTW = Dim-to-Warm (1800K-6500K) 0-10V **RGB+WHITE** RGB = RGB RGBW = RGBW *DMX driver remote mount only.*	**FL LENS** **LO** = 565/ft (5W/ft, 110LPW **SO** = 741/ft (8W/ft, 110LPW **DS1 LENS** LO = 572/ft (5W/ft, 113LPW SO = 762/ft 8W/ft, 108LPW **DR1 LENS** LO = 562/ft (5W/ft, 111LPW) SO = 749/ft (8W/ft, 107LPW **CUSTOM LUMENS** Specify < HO.	**2** = 2 ft 3 = 3 ft **4** = 4 ft 5 = 5 ft **6** = 6 ft 7 = 7 ft **8** = 8 ft For other enter row length (e.g. 48 = 48 ft)	**WM** = Wall Mount	W = White CC = Custom Color AMW = Anti Microbial White	**DIMMING DRIVERS** **DIM10** = 0-10V (1%) - **Standard** DTO = 0-10V (Dim-to-Off) DIMST = 0-10V Step Dimming 347 = 0-10V (347V) DIMSR = DALI Sensor Ready (5.0%) DALI = DALI (5.0%) DMX = DMX (*remote mount only)* **LUTRON™ DIMMING DRIVERS** **LDE1** = Hi-Lume 1% EcoSystem LD2 = Digital 1% (DALI-2) L3DA3W = Hi-Lume 1% 3-Wire **SENSORS & CONTROLS**[4] **EMERGENCY & BATTERY**[5] GTD = Generator Transfer Device EMC = Emergency Circuit EPC4 = 4W Integral Battery **EPC6** = 6.5W Integral Battery EPC10 = 10W Integral Battery EPC12 = 12W Integral Battery **WIRING & OTHER** FWH = Flexible Wiring Harness *Consult factory on Options. Not all are integral to PRFL-22.*

[1]All LED, BIOS, Tunable White, DTW, and RGB options and Ordering Codes page 2.

[2]Lumens at 80CRI, 3500K, FL lens. Photometry page 5.

[3]See page 5 for mounting option details.

[4]All Sensor & Control options page 2.

[5]EPC6 is standard unless otherwise specified. EPC not for DMX drivers.

BAA letter of compliance available at www.dayolite.com.

RS 10 Day Rapid Ship options in **blue**. Details page 6.

LED, BIOS, Sensor & Control Ordering Codes

LED

Static White
30 = 3000K 80 CRI
35 = 3500K 80 CRI
40 = 4000K 80 CRI
50 = 5000K 80 CRI

927 = 2700K 90 CRI
930 = 3000K 90 CRI
935 = 3500K 90 CRI
940 = 4000K 90 CRI

Tunable[1] 2-Channel
2700K-6500K 80 CRI
Fixed CCT Range

2DIM10 = 0-10V
2DMX = DMX 80
2CAS = Casambi Wireless
2ESN = Philips EasySense
2LUT = Lutron (LD2)

92DIM10 = 0-10V 90 CRI
92DMX = DMX 90 CRI
92CAS = Casambi Wireless 90 CRI
92ESN = Philips EasySense 90 CRI
92LUT = Lutron (LD2) 90 CRI

Tunable[1] 3-Channel
1800K-6500K 92 CRI
Selectable range CCT (factory set)

3DIM10 = 0-10V Dimming

Dim-to-Warm[2]
DTW = 6500K-2700K 80 CRI
9DTW = 6500K-2700K 90 CRI

3DTW = 6500K-1800K 92 CRI
Selectable range CCT (factory set).
To specify write in the desired range; eg. 65/18 = 6500K-1800K, or 57/22 = 5700K-2200K.

RGB/W[3]
RGB = RGB only
RGB27 = RGB w/2700K
RGB30 = RGB w/3000K
RGB35 = RGB W/3500K
RGB40 = RGB w/4000K
RGB50 = RGB w/5000K
RGBWW = RGB w/2700K-6500K
ADV = Advanced Color 125mm increment RGB or RGBW pixel control

Single Color
RED = Red
BLU = Blue
GRN = Green
AMB = Amber

BIOS SkyBlue

BIOS SkyBlue biological technology brings the benefits of blue skies inside. BIOS SkyBlue is the only spectrally optimized circadian solution to target the region that drives wellness benefits including: increased alertness, enhanced productivity, better mood, and better sleep. More information may be found at www.bioslighting.com or by contacting Day-O-Lite directly. All options for 0-10V control.

BIOS Biological Static
For daytime applications. BIOS Static Biological LED features key BIOS SkyBlue (490nm) for maximum daytime circadian impact.

B30 = 3000K
B35 = 3500K
B40 = 4000K

BIOS Biological Dynamic White
Designed to transition from daytime to evening in a dim-to-warm protocol. The daytime CCT includes full BIOS SkyBlue (490nm) for maximum daytime circadian impact, while the evening spectrum removes BIOS SkyBlue for minimal circadian stimulus after hours.

B30D = 3000K-2700K
B35D = 3500K-3000K
B40D = 4000K-3500K

BIOS Biological Tunable White
Designed to transition from daytime to evening in a tunable white protocol. The daytime CCT includes full BIOS SkyBlue (490nm) for maximum daytime circadian impact, while the evening spectrum removes BIOS SkyBlue for minimal circadian stimulus after hours.

B30T = 3000K-2700K
B35T = 3500K-2700K
B40T = 4000K-2700K

Sensors & Controls

Sensors*

AVO = Avi-On Occ/Day
AVM = Avi-On Occ (Microwave)
AVN = Avi-On Node
BNV = BubblyNet Occ/Day
LEG = Legrand Occ/Day
ANW = Lutron Athena Occ/Day
VIVE = Lutron Vive Occ/Day
NLT = Acuity nLight Occ/Day
NXC = Current NX Occ/Day
ESN = Philips EasySense Occ/Day
WVL = Cooper WaveLinx Occ/Day

Sensors and control options to be commissioned wirelessly in the field by qualified controls personnel with applicable apps (by others).

Wireless Control

CAS = Casambi

Other Options

Other sensor and wireless control options are available. Contact factory for details.

*Sensors for remote mount only.

[1]Tunable white may be controlled by a number of dimming protocols as shown. 2-Channel has a fixed range of 2700K-6500K. 3-Channel has a maximum range of 1800K-6500K, but other sub-ranges may be specified. 3-Channel Tunable White has a third diode to more closely approximate the black body curve in the mid CCT ranges. Contact Day-O-Lite for details.

[2]Dim-to-Warm mimics incandescent dimming by warming the CCT from 6500K-2700K (2DTW) or 6500K-1800K (3DTW) as light levels are dimmed.

[3]All RGB, RGBW, RGBWW and ADV options for DMX control (by others). 80 CRI standard.

Individual Fixtures & Continuous Rows

NOMINAL LENGTH	ACTUAL LENGTH	SUSP. 1 O.C.	SUSP. 2 O.C.	SUSP. 3 O.C.
4'	3' 8-1/2"	41 1/2"		
8'	7' 5"	86"		
12'	11' 1-1/2"	86"	44 1/2"	
16'	14' 10"	86"	89"	
20'	18' 6-1/2"	86"	89"	44 1/2"
24'	22' 3"	86"	89"	89"

Individual fixtures and rows are continuously illuminated and joined with included aligner brackets and hardware. Power feed locations and mounting locations are shown below.

Continuous rows longer than 8' and patterns, including EPC/EMC and sensor locations must be approved prior to manufacturing. See following page to specify patterns.



Emergency & Sensor Locations

EPC will control entire length of individual fixtures. Individual fixtures of differing lengths will deliver the same lumens under EPC power (a 4' fixture will deliver the same total lumens over half the length of an 8' fixture). **EMC** controlled individual fixtures will deliver lumens per foot as originally specified, unless dimmed at time of power loss. Consult factory for EMC dimming override device.

4' Individual



8' Individual



For individual fixtures to 8' **EPC/EMC** will power entire fixture.

24' Row (3x8')



For continuous rows longer than 8' one **EPC/EMC** will be located in the feed section (end-left) of the row.

24' Row (3x8')



If two **EPC/EMC'**s are required their locations will be in the feed section (end-left) and last section (end-right).

24' Row (3x8')



Custom placement of one or more **EPC/EMC**'s must be clearly identified during ordering.

8' Individual



SENSORS for individual fixtures will control entire length of fixture and will be located on feed end of fixture.

24' Row (3x8')



SENSORS for rows will control the feed section (end-left) of the row. Sensors can control more than an 8' section within a row. Consult factory for sensor/section options, or for multiple sensors in a continuous row.

Pattern Guide

Profile may be specified in patterns of virtually any configuration. All patterns and corners are continuously illuminated and joined with included aligner brackets and joining hardware. See examples below for pattern suggestions. Day-O-Lite's custom manufacturing capabilities allow the specification of custom angled connectors to make arbitrary patterns possible. (See ILX example below).

All corners and connectors are fully welded to ensure correct dimensions and "square" joinery when assembled.

How to Specify

1. Submit your pattern to Day-O-Lite in dimensioned CAD file or submit a fully dimensioned PDF file.
2. If EPC/EMC or Sensors are to be included their location needs to be clearly noted.
3. Day-O-Lite will design your pattern to as close as is nominally possible given standard LED module lengths, including connectors.
4. Day-O-Lite will supply a detailed drawing for approval with final dimensions. All patterns must be approved prior to manufacture.

Pattern Examples









Illuminated Connectors



ILC2 = 90° Corner



ILC3 = 90° Tee



ILC4 = 90° Cross



ILCX = X° Custom

Optics



FL
Flush

DS1
Drop Square

DS2
Drop Square

DR1
Drop Round

DR2
Drop Round

Mounting

Mounting is wall mount to single-gang junction box.



Photometry



PRFL-22-D-**FL**-35-**SO**-4
Flush Lens
4000K CCT
WATTS: 27
LUMENS: 2963
LPW: 110

PRFL-22-D-**DS1**-35-**SO**-4
1" Drop Square Lens
4000K CCT
WATTS: 27
LUMENS: 3046
LPW: 113

PRFL-22-D-**DR1**-35-**SO**-4
1" Drop Round Lens
4000K CCT
WATTS: 27
LUMENS: 2996
LPW: 111

3500K @ 80CRI, 4', FL lens. Download IES files for DR2 and DS2 lenses as www.dayolite.com.
Use the following multipliers for other CCTs: 2700K x 0.96, 3000K x 0.98, 4000K x 1.02, 5000K x 1.03. IES files @ www.dayolite.com

Specifications

CONSTRUCTION: Extruded aluminum housing, 20 gauge cold rolled steel internal components.

REFLECTOR: Highly reflective baked white enamel with pre-finished reflective LED tray.

OPTICS: Frosted acrylic, 1" and 2" drop lens (square) and 1" and 2" drop lens (round).

LED: Static white LED modules in 27/30/35/40 & 50K CCT, 80/90CRI. Lumen maintenance minimum L_{70}= 50,000 hours. 3 SDCM color consistency. BIOS SkyBlue, RGB, RGBW, RGBWW, Tunable White and Dim-to-Warm options available; field replaceable.

DRIVER: Standard driver is Class 2 AOC 0-10V to 1%, Dim-to-Off available. 120/277V input, PF > 90%, THD < 20 @ 120V. DMX, DALI & Lutron protocols available. All drivers prewired for connection to control system (by others), field replaceable.

MOUNTING: Mounting is wall mount to single-gang junction box.

FINISH: Housing and components finished in baked white enamel. Canopies and pendant stems are white enamel unless otherwise specified. 5" feed canopy w/2" suspension canopies.

CERTIFICATION: cETLus listed conforming to UL STD. 1598 and certified to CSA STD C22.2 NO. 250.0. Suitable for dry & damp locations. Union Made in the United States of America, I.B.E.W., BAA compliant, Declare Red List Approved, ADA compliant.

LEGAL: Day-O-Lite, a division of SCW Corporation. All rights reserved. The Day-O-Lite logo is a registered trademark of SCW Corporation. Actual product performance may differ due to end user environment, application and installation. Luminaires have been tested at 25° C ambient temperature. Consult Day-O-Lite for high-ambient conditions. Day-O-Lite reserves the right to change specifications without notice for product improvement.

RS Rapid Ship Program

Rapid Ship products are estimated to ship 10 business days or less from the morning the order is received and confirmed. Linear rows will ship 10 business days or less from the day the layout drawings are approved. Orders confirmed and layouts approved after 12:00 p.m. Eastern Time are estimated to ship 10 days or less from the following business morning. Please refer to complete program Terms & Conditions at www.dayolite.com.

Rapid Ship options are limited to those highlighted in **blue** on the Ordering Guide. 400' max individual or continuous row allowed. Consult factory for additional information.