DAY-O-LITE

Equator Series | EQL-SL-D-2'

Date	Notes
Project	
Type Qty	

Features

Extruded, shallow 2 1/2" aluminum housing.

LED optimized optics for smooth, efficient illumination.

Programmable driver for custom lumen packages.

0-10V dimming to 1% standard or Dim-to-Off.

DMX, Lutron and DALI protocols also available.

Sensor Ready for wireless Smart Lighting Solutions.

ADA compliant wall mount luminaire.

Declare Red List Approved.





Ordering Guide

Declare. BAA

MODEL	OPTICS	CCT	LUMENS[1]	DIAMETER	MOUNTING[2]	FINISH	OPTIONS
EQL-SL-D				**2**			
EQL-SL-D Direct	**STANDARD** SI = Satin Ice Flat Acrylic lens.	27 = 2700K 90CRI* 30 = 3000K 80CRI 35 = 3500K 80CRI 40 = 4000K 80CRI 50 = 5000K 80CRI 90 CRI add "9" Ex: 940 = 4000K @ 90 CRI. 2700K always 90 CRI	**SI LENS (Flat)** LO = 1426 (15W, 95LPW) SO = 1876 (20W, 94LPW) HO = 2325 (25W, 93LPW) **CUSTOM** Specify < HO. Ex: Enter 1900 for 1900 Lumens.	2 = 23"	AC = Aircraft Cable PD = Pendant Stem ACM = Mono-Point S = Surface WM = Wall Mount	W = White CC = Custom Color AMW = Anti-Microbial White	**DIMMING DRIVERS** DIM10 = 0-10V (1%) Standard DTO = 0-10V (Dim-to-Off) DIMST = 0-10V Step Dimming DIMSR = DALI Sensor Ready (5.0%) DALI = DALI (5.0%) DMX = DMX **LUTRON™ DIMMING DRIVERS** LDE1 = Hi-Lume 1% EcoSystem LD2 = Digital 1% (DALI-2) L3DA3W = Hi-Lume 1% 3-Wire **SENSORS & CONTROLS[3]** AVO = Avi-On Sensor AWNS = Lutron Athena Sensor ESN = EasySense Sensor CAS = Casambi Wireless Control **EMERGENCY[4]** EMC = Emergency Circuit GTD = Generator Transfer Device EPC4 = 4W Emergency Battery EPC6 = 6.5W Emergency Battery EPC10 = 10W Emergency Battery EPC12 = 12W Emergency Battery **WIRING** FWH = Flexible Wiring Harness

[1]Lumens at 80CRI, 4000K, SI lens. Photometry page 2.

[2]See page 2 for mounting option details.

[3]All sensors remote mount only.

[4]EPC6 is standard unless otherwise specified. EPC not for DMX drivers.

BAA letter of compliance available at www.dayolite.com.

Suspensions

Standard suspension options include adjustable self-locking aircraft cables (AC), a 3-into-1 monopoint (ACM) and rigid pendant stems (PD). AC assembly is 48" x 1/16" with a 5" feed canopy and 2" suspension canopies. 60" 18 gauge power and 22 gauge dimming control SJT feed.

PD assemblies are 5/8" dia. (or 3/8" IP) hollow stem for power feed by others, 24" is standard.



S
Surface
Mount

ACM
Monopoint
48" O.A.

AC
Aircraft Cable
48" Length

PD
Pendant Stem
24" Length

Consult factory for longer ACM, AC and PD suspension lengths.

See page 4 for number of AC & PD suspension points per diameter..

All feed canopies 5" dia., all non-feed canopies 2" dia.

All canopies white unless requested otherwise.

Photometry



EQL-SL-D-SI-40-**LO**-2

4000K CCT
WATTS: 15
LUMENS: 1426
LPW: 95
Distribution:
100% Direct

EQL-SL-D-SI-40-**SO**-2

4000K CCT
WATTS: 20
LUMENS: 1876
LPW: 94
Distribution:
100% Direct

EQL-SL-D-SI-40-**HO**-2

4000K CCT
WATTS: 25
LUMENS: 2325
LPW: 93
Distribution:
100% Direct

40000K @ 80CRI, SI lens.
Use the following multipliers for other CCTs: 2700K x 0.94, 3000K x 0.96, 3500K x 0.98, 5000K x 1.02. IES files @ www.dayolite.com

Specifications

HOUSING: One-piece aluminum spinning for a clean seamless appearance.

REFLECTOR: Die-formed, 20-gauge, cold rolled steel in high gloss baked white enamel.

OPTICS: Satin Ice Acrylic flat lens standard.

LEDS: LED modules in 27/30/35/40 & 50K CCT, 80 CRI (90CRI available). Lumen maintenance minimum L_{70}= 50,000 hours. 3 SDCM color consistency. Zhaga compliant (Book 7). Field replaceable.

DRIVER: Standard driver is Class 2 AOC 0-10V to 1%, 120/277V input, PF > 90%, THD < 20 @ 120V. Additional dimming protocols available. All drivers prewired from factory for connection to control system (by others). Field replaceable.

MOUNTING: Standard options include adjustable self-locking aircraft cables (AC), monopoint (ACM) and rigid pendant stems (PD). AC assembly is 48" x 1/16" with a 5" feed canopy and 2" suspension canopies. 18 gauge power and 22 gauge dimming control SJT feed. A 3-into-1 monopoint is also available.

FINISH: Housing and components finished in baked white enamel. Canopies and pendant stems are white enamel unless otherwise specified. 5" Feed canopy w/2" Suspension canopies.

CERTIFICATION: Luminaires are cETLus listed conforming to UL STD. 1598 and certified to CSA STD C22.2 NO. 250.0. Suitable for dry & damp locations. Union Made in the United States of America. I.B.E.W., BAA compliant, Declare Red List Approved.

LEGAL: Day-O-Lite, a division of SCW Corporation. All rights reserved. The Day-O-Lite logo is a registered trademark of SCW Corporation. Day-O-Lite reserves the right to change specifications without notice for product improvement.